

PONDICHERRY UNIVERSITY
ENGINEERING WING

SCHEDULE OF WORK

Name of the work Maintenance to the Guest house II

Sl No:	Description	Qty	Rate	Unit	Amount
1 15.3 9.1	Dismantling wooden boardings in lining of walls and partitions , excluding supporting members but including stacking within 50 metres lead - upto 10mm thick	630.00		sqm	
2 13.5 0.1	Applying priming coat - with ready mixed pink or grey primer of approved brand and manufacture on wood work (hard and soft wood	630.00		sqm	
3 13.6 2.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade - Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture	630.00		sqm	
4 17.2. 1	Providing and fixing white vitreous china pedestal type water closet (European type W.C.pan) with seat and lid, 10 litre low level white P.V.C. flusing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS: 7231,with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required - W.C. pan with ISI marked white solid plastic seat and lid	2.00		each	
5 17.3 1	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6mm thick hard board ground fixed to wooden cleats with C.P.brass screws and washers complete	2.00		each	
6 18.7. 2	Providing and fixing Chlorinated Polyvinnyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings including fixing the pipe with clamps at 1.00m spacing.This includes jointing of pipes	155.00		metre	

	& fittings with one step CPVC solvent cement and testing of joints complete - internal work - exposed on wall - 20 mm nominal outer dia pipes				
7 18.9. 13	Providing and fixing ASTM pipes including all ASTM plain& brass threaded fittings i/cfixing the pipe with clamps at 1.00m spacing . This includes jointing of pipes & fitting with one step ASTM solvent cement and testing of joints complete (Internal work exposed on wall) - 32mm nominal outer dia pipes	155.00		metre	
8 18.9. 15	Providing and fixing ASTM pipes including all ASTM plain& brass threaded fittings i/c fixing the pipe with clamps at 1.00m spacing . This includes jointing of pipes & fitting with one step ASTM solvent cement and testing of joints complete (Internal work exposed on wall) - 50mm nominal outer dia pipes	40.00		metre	
9 18.1 7.4	Providing and fixing gun metal gate valve with C.I.wheel of approved quality (Screwed end) - 50 mm nominal bore	2.00		each	
10 18.1 7.2	Providing and fixing gun metal gate valve with C.I.wheel of approved quality (Screwed end) - 32mm nominal bore	17.00		each	
11 18.5 3.1	Providing and fixing C.P.brass angle valve for basin mixer and geyser points of approved quality conforming to IS: 8931- 15 mm nominal bore	25.00		each	
12 18.5 1.1	Providing and fixing C.P.brass long body bib cock of approved quality conforming to IS standards and weighing not less than 690 gms - 15 mm nominal bore	5.00		each	
13 18.4 9.1	Providing and fixing C.P.brass bib cock of approved quality conforming to IS: 8931 - 15 mm nominal bore	34.00		each	
14 17.7 8.1	Providing and fixing CP brass health faucet of approved quality - 15 mm nominal bore	5.00		each	
15	Providing and fixing un plasticised	34.00		each	

18.7 4.2	P.V.C. connection pipe with PTMT nuts, collar, and bush of approved quality and colour - 15 mm nominal bore with 45cm length				
16 18.2 1.2.1	Providing and fixing unplasticised PVC connection pipe with brass unions - 45 cm	34.00		each	
17 17.2 8.2.2	Providing and fixing P.V.C. waste pipe for sink or wash basin including PVC waste fittings complete - flexible pipe - 40mm dia	20.00		each	
18 17.7. 2	Providing and fixing wash basin with C.I. brackets, 15mm C.P. brass pillar taps ,32 mm C.P.brass waste of standard pattern , including painting of fittings and brackets ,cutting and making good the walls wherever required - white Vitreous China wash basin size 630x450 mm with a single 15 mm C.P.brass pillar taps	1.00		each	
19 9.84	Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564 , embossed on the body, door weight upto 36 kg to 80 kg and door width from 701 mm to 1000 mm) , with double speed adjustment with necessary accessories and screws etc.complete	4.00		each	
20 9.81. 1	Providing and fixing bright finished brass handles with screws etc complete - 125 mm	68.00		each	
21 9.81. 3	Providing and fixing bright finished brass handles with screws etc complete - 75 mm	34.00		each	
22 9.82	Providing and fixing bright finished brass hanging type floor door stopper with necessary screws etc complete	17.00		each	
23 9.79. 3	Providing and fixing special quality bright finished brass cupboard or ward robe locks with four levers of approved quality including necessary screws etc complete - 65mm	34.00		each	
24 9.79.	Providing and fixing special quality bright finished brass cupboard or ward robe locks with four levers of approved	34.00		each	

1	quality including necessary screws etc complete - 40mm				
25 18.2 2.1	Providing and fixing C.P.brass shower rose with 15 or 20 mm inlet - 100 mm diametre	17.00		each	
26 18.1 6.2	Providing and fixing brass stop cock of approved quality - 20mm nominal bore	17.00		each	
27 MR	Providing and fixing pillar cock of approved quality and colour - 15 mm nominal bore , 107 mm long, weighing not less than 110 gms(Parry ware)	4.00		each	
	TOTAL				

I hereby abide the rules and regulations stipulated in the CPWD form no. 6 & 8.

Contractor

Executive Engineer