PONDICHERRY UNIVERSITY ENGINEERING WING

SCHEDULE OF WORK

<u>Name of the work:</u> Maintenance of external water supply pipelines at Administrative building Pondicherry University

| S. No. | Description | Qty. | Rate Rs.P. | Unit | Amount Rs.P. |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------|-------|-----------------|
| 1. M.R | Providing and fixing ASTM pipes - 90 mm dia pipes, having thermal stability for hot & cold-water supply, including all ASTM pipes plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step ASTM pipes solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 90 mm nominal outer dia pipes | 140.00 | | Metre | |
| 2. 18.9. 15 | Providing and fixing ASTM pipes including all ASTM plain & brass threaded fittings i/c fixing the pipe with clamps at 1.00m, spacing. This includes jointing of pipes & fitting with one step ASTM solvent cement and testing of joints complete (Internal work exposed on wall) - 50mm nominal outer dia pipes | 255.00 | | metre | |
| 3. 18.9. 13 | Providing and fixing ASTM pipes including all ASTM plain & brass threaded fittings i/c fixing the pipe with clamps at 1.00m spacing. This includes jointing of pipes & fitting with one step ASTM solvent cement and testing of joints complete (Internal work exposed on wall) - 32mm nominal outer dia pipes | 100.00 | | metre | |
| 4. 18.1 7.6 | Providing and fixing gun metal gate valve with C.I.wheel of approved quality (Screwed end) - 80mm nominal bore | 6.00 | | each | |
| 5 18.1 7.4 | Providing and fixing gun metal gate valve with CI wheel of approved quality (screwed end) - 50 mm nominal bore | 16.00 | | each | |
| 6. 18.7 | Cutting holes upto 30x30 cm in walls including making good the same with | 20.00 | | each | |

| 6.1 | FPS bricks | | | |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------|--|
| 7. 15.4 4. 1 | Dismantling G.I.pipes (external work) including excavation and refilling trenches after taking out the pipes, manually / by mechanical means including stacking of pipes within 50 metres lead- 15mm to 40mm | 255.00 | metre | |
| 8. 15.4 4.2 | Dismantling G.I. Pipes (external work) including excavation and refilling trenches after taking out the pipes manually / by mechanical means including stacking of pipes within 50m lead - Above 40mm nominal bore. | 140.00 | metre | |
| 9. 6.4.1 | Brick work with common burnt clay F.P.S (non modular) bricks of class designation 7.5 in superstructure above plinth level upto floor five level in all shapes and sizes in - cement mortar 1:4 (1 cement: 4 coarse sand) | 2.00 | cum | |
| 10. 13.8. 2 | 15 mm cement plaster on rough side of single or halfbrick wall finished with a floating coat of neat cement of mix - 1:4 (1 cement : 4 fine sand | 8.00 | sqm | |
| 11. 13.3 9.1 | Colour washing such as green, blue or buff to give an even shade - New work (two or more coats) with a base coat of white washing with lime | 8.00 | sqm | |
| 12. 18.7 7 | Cutting holes upto 15x15 cm in R.C.C floors and roofs for passing drain pipe etc. andrepairing the hole after insertion of drain pipe etc with cement concrete 1:2:4 (1 cement : 2 coarse sand: 4 graded stone aggregate 20 mm nominal size)including finishing complete so as to make it leak proof | 6.00 | each | |
| 13. 14.7 2 | Providing and fixing double scaffolding system (cup lock type) on the exterior side, upto seven story height made with 40mm dia M.S. tube 1.5m centre to centre horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it is a serviceable condition for the required duration as approved and removing it thereafter. The scaffolding system shall be stiffened with bracings, runners, | 168.00 | sqm | |

| connection with the building etc. | |
|-------------------------------------------|--|
| wherever required for inspection of | |
| work at required locations with essential | |
| safety features for the workmen etc. | |
| complete as approved.the elevational | |
| area of the scaffolding, shall be | |
| measured for payment purpose. The | |
| payment will be made once irrespective | |
| of duration of scaffolding. (To be used | |
| for maintenance work judicially | |
| necessary deduction for scaffolding in | |
| the existing item to be done) | |
| | |
| TOTAL | |
| | |

I hereby abide the rules and regulations stipulated in the CPWD form no. 6 & 8.

Contractor

Executive Engineer