

**PONDICHERRY UNIVERSITY**  
**ENGINEERING WING**  
**SCHEDULE OF WORK**

Name of work: Annual maintenance and special repair works to C-1 and C-6 quarters

<b>S. No.</b>	<b>Description</b>	<b>Qty.</b>	<b>Rate Rs.P.</b>	<b>Unit</b>	<b>Amount Rs.P.</b>
1. 14.43	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	350		sqm	
2. 13.43.1	Applying one coat of water thinnable cement primer of approved brand and manufacturer on wall surface - water thinnable cement primer	350		sqm	
3. AR	Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade- two or more coats on old work	350		Sqm	
4. 15.13.1	Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead - of area 3 sqm and below	2		each	
5. 15.12.1	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead - of area 3 sqm and below	3		each	
6. 9.21.2	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part 1) non - decorative type, core of block board construction with frame of 1 st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters - 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	2		sqm	
7. 9.23	Extra for providing lipping with teak wood battens 25 mm minimum depth on all edges of flush door shutters (over all area of door shutter to be measured)	2		sqm	
8. 9.1.2p	Providing wood work in frames of doors , windows, clerestory windows and other frames , wrought framed and fixed in position with hold fast lugs or	0.10		cum	

	with dash fasteners of required dia & length (hold fast lugs or dash fastener shall be paid for separately) -Padak wood				
9. MR	Replastering and finishing the damaged/dismantled cutting portion of the door and window frame wall wherever required including paint finish etc. complete as directed	2		No.	
10. 9.16.1.1p	Providing and fixing 25 mm thick shutters for cup board etc - panelled or panelled & glazed shutters - Padak wood including ISI marked anodised aluminium butt hinges with necessary screws.	4		sqm	
11. 9.9.1.2p	Providing and fixing glazed shutters for doors , windows and clerestory windows using 4 mm thick float glass panes including ISI marked M.S.pressed butt hinges bright finished of required size with necessary screws -Padak wood - 30 mm thick	1		sqm	
12. 9.120.1	Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S.tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15 x15 mm for top & bottom rails. M.S.frame shall have a coat of steel primers of approved make and manufacture . M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top , bottom and lock rails shall be provided both side of the panel. 10mm (5 mm x 2) thick , 20 mm wide cross PVC sheet be provided as gap insert for top rail & bottom rail , panelling of 5 mm thick both side PVC sheet to be fitted in the M.S. frame welded / sealed to the	2		sqm	

	styles & rails with 7 mm (5 mm + 2 mm) thick x 15 mm wide PVC sheet beading on inner side , and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C" Channel using PVC solvent adhesive etc. complete manufacturer's specification & drawing - 30mm thick plain PVC door shutters				
13. 18.9.12	Providing and fixing ASTM pipes including all ASTM plain& brass threaded fittings i/c fixing the pipe with clamps at 1.00m spacing . This includes jointing of pipes & fitting with one step ASTM solvent cement and testing of joints complete (Internal work exposed on wall ) - 25mm nominal outer dia pipes	18		metre	
14. 18.63	Providing and fixing PTMT angle stop cock 15 mm nominal bore, weighing not less than 5 gms	4		each	
15. 18.54.1	Providing and fixing PTMT bib cock of approved quality and colour - 15mm nominal bore, 86 mm long , weighing not less than 88gms	5		each	
16. 18.64	Providing and fixing PTMT swivelling shower, 15mm nominal bore, weighing not less than 40 gms	2		each	
17. 17.18.1	Providing and fixing P.V.C.low level flushing cistern with manually controlled device (handle lever) conforming to IS:7231, with all fittings and fixtures complete - 10 litre capacity -white	1		each	
18. 17.20.1	Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete - white solid plastic seat with lid	1		each	
19. AR	Providing and fixing ASTM valve of approved quality – 25 mm dia	3		No.	
20. 17.31	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6mm thick hard board ground fixed to wooden cleats with C.P.brass screws and washers complete	2		each	
21. 16.100	Acid cleaning for the existing Mosaic floors , glazed tiles work and removing the stains and decays to give a glassy look	31		sqm	

	etc complete (The Acid used shall be 32% concentrated hydrochloric acid after taking on the precautionary measures)				
22. 18.56.1	Providing and fixing PTMT pillar cock of approved quality and colour - 15 mm nominal bore , 107 mm long, weighing not less than 110 gms	1		each	
23. 17.7.6	Providing and fixing wash basin with C.I. brackets, 15mm C.P. brass pillar taps ,32 mm C.P.brass waste of standard pattern , including painting of fittings and brackets ,cutting and making good the walls wherever required - white vitreous china angle back wash basin size 400x400 mm with single 15mm C.P. brass pillar tap	1		each	
24. 17.1.1	Providing and fixing water closet squatting pan (Indian type W.C.pan) with 100 mm Sand Cast Iron P or S trap, 10 litre low level white P.V.C flushing cistern, including flush pipe , manually controlled device (handle lever) conforming to IS : 7231 , with all fittings and fixtures complete , including cutting and making good the walls and floors wherever required. White vitreous china Orissa pattern W.C.pan of size 580x440mm with integral type foot rests.	1		each	
25. 15.23.1	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead – for thickness of tiles 10mm to 25mm	2		sqm	
26. 17.10.1.3	Providing and fixing Stainless steel AISI 304 (18/8) kitchen sink as per IS 13983 with C.I.brackets and stainless steel plug 40mm , including painting of fittings and brackets, cutting and making good the walls wherever required - kitchen sink with drain board - 510x1040 mm bowl depth 200mm	2		each	
27. 11.38.2	Providing and laying ceramic glazed floor tiles of size 300 x 300 mm (thickness to be specified by the manufacturer) , of commercial quality conforming to IS :15622, of approved make (Bell / Johnson / Regency / Somany / Naveen / Asian) in all colours,shades,	2		sqm	

	except white , ivory, grey, fume red brown, laid on 20 mm thick bed of cement mortar 1:4 (1 cement : 4 coarse sand), including pointing the joints with white cement and matching pigments etc., complete				
28. 16.90	Poiling the existing mosaic floor with Power polisher to a high degree of polish as to be perfectly smooth	49		sqm	
29. 2.35.4.1	Diluting and injecting chemical emulsion for POST - CONSTRUCTIONAL anti-termite treatment (excluding the cost of chemical emulsion) - Treatment of existing masonry using chemical emulsion @ one litre per hole at 300mm interval including drilling holes at 45 degree and plugging them with cement mortar 1:2 ( 1 cement : 2 coarse sand) to the full depth of the hole – with chlorpyrifos / lindane E.C. 20% with 1% concentration	42		metre	
30. 2.34.1	Supplying chemical emulsion in sealed containers including delivery as specified - Chlorpyrifos / lindane emulsifiable concentrate of 20%	7		litre	
31. 14.54.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade - One or more coats on old work	130		sqm	
32. 14.53.1C	Wall painting with plastic emulsion Commercial - of approved brand and manufacture to give an even shade - One or more coats on old work	90		sqm	
33. 13.50.1	Applying priming coat- with ready mixed pink or grey primer of approved brand and manufacture on wood work ( hard and softwood)	16		sqm	
34. 13.61.1	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade - Two or more coats on new work	16		sqm	
35. 9.100.1	Providing and fixing aluminium handles , ISI marked , anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade,with necessary screws etc, complete - 125 mm	7		each	
36. 9.97.4	Providing and fixing aluminium tower bolts , ISI marked ,	4		each	

	anodised (anodic coating not less than grade AC 10 as per IS :1868) , transparent or dyed to required colour or shade , with necessary screws etc. complete - 150 x10 mm				
37. 9.97.3	Providing and fixing aluminium tower bolts , ISI marked , anodised (anodic coating not less than grade AC 10 as per IS :1868) , transparent or dyed to required colour or shade , with necessary screws etc. complete - 200 x10 mm	4		each	
38. 9.96.2	Providing and fixing aluminium sliding door bolts , ISI marked , anodised ( anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade , with nuts and screws etc complete - 250 X 16 mm	3		each	
39. 9.97.2	Providing and fixing aluminium tower bolts , ISI marked , anodised (anodic coating not less than grade AC 10 as per IS :1868) , transparent or dyed to required colour or shade , with necessary screws etc. complete - 250 x10 mm	2		each	
40. 14.6.1B	Renewing glass panes, with wooden fillets wherever necessary - Float glass panes of thickness 4mm	1		sqm	
41. 15.2.2	Demolishing cement concrete manually / by mechanical means including disposal of material within 50 metres lead Nominal concrete 1:4:8 or leaner mix (including equivalent design mix)	1		cum	
42. 4.1.3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - all work upto plith level - 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size)	2		cum	
43. 5.9.1	Centering and shuttering including strutting , propping etc and removal of form for - foundations, footings, bases of columns etc for mass concrete	1		sqm	
44. 13.1.2	12mm cement plaster of mix - 1:6 ( 1 cement : 6 fine sand)	1		sqm	
45. 17.28.2.1	Providing and fixing P.V.C. waste pipe for sink or wash basin including PVC waste fittings complete - flexible pipe - 32mm dia	2		each	

46. 18.74.2	Providing and fixing unplasticised P.V.C. connection pipe with PTMT nuts, collar, and bush of approved quality and colour - 15 mm nominal bore with 45cm length	2		each	
47. 9.53	Providing 40 X 5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30 x10 x 15 cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size)	4		each	
	<b>Total</b>				

**Terms & Conditions:**

- i) The rates specified are firm and not subject to any variation.
- ii) The work should be completed within 20 days.
- iii) Payment will be made only after completion of the entire work.
- iv) The material should be got approved before commencement of work.
- v) The rate specified should be inclusive of GST.

**Contractor**

**Executive Engineer**