

PONDICHERY UNIVERSITY

ENGINEERING WING

SCHEDULE OF WORK

Name of the work: Replacing the damaged doors and providing anti termite treatment and internal painting at F-7 and F-29 quarters building

S. No.	Description	Qty.	Rate Rs.P.	Unit	Amount Rs.P.
1. 15.1 2.1	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead - of area 3 sqm and below	2		each	
2. 9.1.2 p	Providing wood work in frames of doors , windows, clerestory windows and other frames , wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length (hold fast lugs or dash fastener shall be paid for separately) -Padak wood	0.15		cum	
3. 9.53	Providing 40 X 5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30 x10 x 15 cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size)	8		each	
4. AR	Replastering and finishing the damaged cutting portion of the door frame wall around including paint finish etc, complete as directed	2		No.	
5. 9.21. 2	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part 1) non - decorative type, core of block board construction with frame of 1 st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters - 30 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	4		sqm	
6. 9.23	Extra for providing lipping with teak wood battens 25 mm minimum depth on all edges of flush door shutters (over all area of door shutter to be measured)	4		sqm	
7. 9.97. 3	Providing and fixing aluminium tower bolts , ISI marked , anodised (anodic coating not less than grade AC 10 as per IS :1868) , transparent or dyed to required colour or shade , with necessary screws etc. complete - 200 x10 mm	4		each	
8.	Providing and fixing aluminium handles , ISI marked , anodised (anodic coating	4		each	

9.10 0.1	not less than grade AC 10 as per IS : 1868 transparent or dyed to required colour or shade,with necessary screws etc, complete - 125 mm				
9. 9.96	Providing and fixing aluminium sliding door bolts , ISI marked , anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade , with nuts and screws etc complete - 250 X 16 mm	2		each	
10. 13.5 0.1	Applying priming coat - with ready mixed pink or grey primer of approved brand and manufacture on wood work (hard and soft wood)	9		sqm	
11. 13.6 1.1	Painting with synthetic enamel paint of approved brand and manufacutre to give an even shade - Two or more coats on new work	9		sqm	
12. 2.35. 4.1	Diluting and injecting chemical emulsion for POST - CONSTRUCTIONAL anti-termite treatment (excluding the cost of chemical emulsion) - Treatment of existing masonry using chemical emulsion @ one litre per hole at 300mm interval including drilling holes at 45 degree and plugging them with cement mortar 1:2 (1 cement : 2 coarse sand) to the full depth of the hole – with chlorpyriphos / lindane E.C. 20% with 1% concentration	141		metre	
13. 2.35. 5	Diluting and injecting chemical emulsion for POST - CONSTRUCTIONAL anti-termite treatment (excluding the cost of chemical emulsion) - treatment at points of contact of wood work by chemical emulsion Chlorpyriphos / Lindane (in oil or kerosene based solution) @ 0.5 litres per hole by drilling 6mm dia holes at downward angle of 45 degree at 150mm centre to centre and sealing the same	180		metre	
14. 2.34. 1	Supplying chemical emulsion in sealed containers including delivery as specified - Chlorpyriphos / lindane emulsifiable concentrate of 20%	54		litre	
15. 14.4 3	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scrarches etc.complete	342		sqm	
16. 13.4 3.1	Applying one coat of water thinnable cement primer of approved brand and manufacturer on wall surface - water thinnable cement primer	342		sqm	

17. AR	Wall painting with plastic emulsion of approved brand and manufacture to give an even shade – two or more coats on old work	342		Sqm	
18. 13.2 6A	Providing and applying ready mixed wall putty (JK / Birla) of 2 mm thickness over plastered surface to prepare the surface even and smooth complete	31		sqm	
19. 14.5 4.1	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade - One or more coats on old work	113		sqm	
20. 14.7 0	Melamine polishing on wood work (one or more coat)	72		sqm	
	Total				

Terms & Conditions:

- i) The rates specified are firm and not subject to any variation.
- ii) The work should be completed within 30 days.
- iii) Payment will be made only after completion of the entire work.
- iv) The material should be got approved before commencement of work.
- v) The rate specified should be inclusive of GST.

Contractor

Executive Engineer